Technical data
KF 4

Revision no	Page:
	1

Receiver	From
Company name	
Respons. Department	
Person in charge	
Phone number	
Fax no	
E-mail address	



Operating data specification

Nominal flow	m³/h	0
Nominal head	m	0
Static head	m	0
NPSH - value of plant	m	0
Inlet pressure	bar	0,09793
Fluid		Water, pure
Operating temperature t A	°C	20
Density at t A	kg/m³	998,3
Kin. viscosity at t A	mm²/s	1,005

Pump

Pump name			KF 4	
Size				
Design				
Speed rpm		2850	No of stages 1	
Impeller type			Peripheral impeller	
Flow	Nominal		m³/h	
	Max-		m³/h	2,99
	Min-		m³/h	1
Head	Nominal		m	
	Max-		m	52,2
	Min-		m	10,9
Head H(Q=0)			m	79,8
NPSH 3%			m	
Max. working pressure			bar	7,82
Shaft power			kW	
Efficiency			%	
Max absorbed power			kW	0,88426

Materials Pump

Shaft	Stainless steel AISI 420 (1.4028)
Impeller	Brass
Pump body	Cast iron EN-GJL-200
Support	Cast iron EN-GJL-200
OR	NBR Rubber
Mechanical seal	BXPG (Gra/Cer/NBR)

Motor					
Manufacturer / Type		SAER 80 2 - 0,75 3~			
Rated power	kW	0,75	Efficiency 4/4		0 %
Electric current	A	4,8 A	Speed	rpm	2950
Electric voltage	V	230 V	3~	Hz	50
Starting mode		Unknown			
Degree of protection		IP 44	Insulation class		F

Dimensions in mm

a	45
DNA	G 1"
DNM	G 1"
f	240,5
H	180
h1	71
h2	161
m1	112
m2	90
n1	135
n2	112
od	7
w	64,5



Remarks:

Project	Project ID	Created by	Created on	Last update
			2019-02-13	